Security Key Box with removable shackle


SSZ 200B











Access for changing people

Protective cover



ASSEMBLY/OPERATING INSTRUCTIONS







General notes

Intended use

Please read the usage and maintenance instructions carefully before mounting the security key box with removable shackle. Keep the manual with you for future use. If the product is passed on to any third party, include the manual with it.



Warning: No hazards should be expected if the product is assembled and operated professional-

ly and in accordance with the manual. Small parts and packaging materials can be swallowed by children and lead to choking! Make sure that small parts and packaging materials do not get into the hands of children. Dispose of the packaging material immediately.

Please read the operating manual before using the device. It is important to note that the security key box with removable shackle MAY NOT be dismantled. Please handle the device with care.

The manufacturer expressly reserves the right to make technical changes.

Disclaimer

The manufacturer accepts no liability for damage or injury resulting from incorrect handling.

Dis

Disposal

Help to protect the environment and dispose of the product and the packaging materials in accordance with the local regulations. Do not dispose of the device in household waste!

ASSEMBLY:

Step 1:

Open the key safe by setting the digits (3) to the starting position 0-0-0-0 and then pressing the opener (2). Now pull the door of the safe towards you.

Step 2:

Mark the drill holes at the desired drilling location. Please use the back of the key safe as a template.



Step 3:

Drill the holes.



ATTENTION!

Make sure that cables or pipes are not routed along at the selected drilling point. This can pose a risk of injury or of damage to the surrounding area.


Step 4:

Insert the dowels into the drill holes.



NOTE:

Note that the supplied fastening material might prove to be unsuitable for the desired mounting location. You can purchase fastening material that corresponds to your needs from the DIY store.





Step 5:


Hold the security key box against the drill holesand fasten the screws into the dowels with the help of a screwdriver. Screw the key safe in place.

Scope of delivery:

- Security key box
- Mounting material
- Operating manual

Product details

- 1 Lock
- 3 Digits
- ② Opener
- (4) Reset switch



Technical specifications	
Housing	Aluminium
Coating	Rust-proof treated
Security combination lock	with 4 digits Up to 10,000 combinations possible
Outside dimensions	H185 x W90 x D40 mm
Shackle height and width	H59 x W39 mm
Weight	560 g

Change the numeric password

- 1. Set the reset switch (4) to position B.
- 2. Set your desired 4-digit numeric password and make a note of it.
- Set the reset switch (4) back to position
 Your new numeric password is now set.
- 4. Close the door of the key safe.

Opening and closing of the shackle

- 1. Open the SSZ 200B as described under point 1 during assembly.
- 2. Press lever H to the left and pull the shackle upwards.
- 3. You can now hang the shackle on gates, fences, eyelets, door knobs, etc.
- 4. Now take the SSZ 200B, push lever H to the left and reinsert the shackle.



© Copyright

Reproduction or duplication (even excerpts thereof) is forbidden without approval of: BASI GmbH Konstantinstraße 387 41238 Mönchengladbach Germany

2024

This publication, including all its parts, is protected by copyright.

Any use outside the narrow limits of copyright law without the consent of BASI GmbH is not allowed and liable to prosecution.

This applies in particular to duplications, translations, microfilming and the feeding and processing in electronic systems.

BASI GmbH Konstantinstraße 387 41238 Mönchengladbach Germany